

iD MIXONOMI JEWELS

TECHNICAL DATA

Certification & classification	Standards	iD Mixonomi Jewels	
Type of floor covering	EN ISO 10582	Heterogeneous Compact Resilient Floorcovering	
Classification	EN ISO 10874	Domestic: 23	Commercial: 34 Industrial: 43
Technical characteristics			
Total thickness	EN ISO 2434	2.5 mm	
Wear layer thickness	EN ISO 24340	0.7 mm	
Total weight	EN ISO 23997	4000 g/m ²	
Wear layer binder content	EN ISO 10582		
Dimensions	EN ISO 24342	Lozenge	38.486 x 66.66 cm
		Oblique Left	8.33 x 38.486 cm
		Oblique Right	8.33 x 38.486 cm
		Asscher / Cushion	33.33 x 38.486 cm
		Baguette	10 x 50 cm
		Cleave / Radiant / Table	25 x 25 cm
		Trapezoid	16.66 x 38.486 cm
		Trillion	19.243 x 19.243 cm
		Crown / Pavilion	38.486 x 38.486 cm
Surface treatment (PUR)		Yes, TopCleanXP™	
Beveled edges		No	
Technical performances			
Dimensional stability	EN ISO 23999	≤ 0.10 %	
Curl resultant to heat	EN ISO 23999	≤ 2 mm	
Reaction to fire	EN 13501-1	B _{fl} -s1 glued over concrete substrate B _{fl} -s1 glued over wood substrate	
Residual indentation	EN ISO 24343-1	≤ 0.05 mm	
Furniture leg	EN 424	No damage	
Castor chair	ISO 4918 - EN 425	No damage	
Impact sound reduction	EN ISO 717-2	ΔL _w = 2 dB	
Reduction of in-room impact noise	EN ISO 31-074	Class C (L _{n,e,w} < 85 dB)	
Thermal resistance	EN ISO 10456	0.02 m ² K/W	
Light fastness	EN ISO 105-B02 (method 3a)	≥ 6	
Chemical resistance	EN ISO 26987	Not affected (0)	
Slip resistance	DIN 51130 EN 13893	R10 μ ≥ 0.30	
Electrical properties	EN 1815 EN 1081	<2 kV on concrete > 10 ⁹ Ohm	
Peeling resistance	EN ISO 24345	≥ 50N / 50mm	
Underfloor heating		Suitable - max. 27 °C	

The above information is subject to modification for the benefit of further improvement. (07/18).

Tarkett's instructions regarding installation, cleaning and maintenance should be observed.

Please contact Tarkett at the address shown for these instructions.

CUSTOMS TARIFF : 4820 5000 00

